

Sensors with integrated amplifier | SCB 450 GSP

- DN25 Triclamp plug-in sensor for flow monitoring in liquid media
- Corrosion-proof stainless steel housing AISI 316 Ti
- Immersion depth 55 mm
- LED line for flow status
- M12 plug system
- PNP-NO switching output
- Adjustment with potentiometer
- Corresponds to the requirements of 3A
- Flow monitoring in the food industry




TriClamp 50,5 mm - sensor length 55 mm - PNP-NO - M12 connector

TYPE	SCB 450 GSP
Product ID	P11156
Medium	Water, oil
Detection range water	1 ... 150 cm/s
Detection range Oil	3 ... 300 cm/s
Process connection	Triclamp Ø 50,5 mm
Output	switching output
Output function	PNP-NO
Supply voltage	24 VDC +/- 20 %
Current consumption max.	70 mA
Switching current max.	400 mA (20 °C)
Reverse polarity protection	✓
Voltage drop max.	2.5 V
Ambient temperature	-20 ... 80 °C
Medium temperature	-20 ... 80 °C
Temperature gradient fluids	250 K/min
Start-up time typ.	8 s (2 ... 15 s)
Reaction time typ.	2 s (1 ... 13 s)

Compressive strength	100 bar
Material sensor touched by medium	stainless steel AISI 316 L
Material housing	stainless steel AISI 303, stainless steel AISI 316 L, PA
Surface roughness less than	0.8 µm
Protection [EN 60529]	IP 67
Electrical connection	M12 connector
Accessories	connecting cable SLG 3-2, SLG 3-5, SLW 3-2, SLW 3-5
Accessories (in scope of delivery)	screwdriver

Technical Image



Pin Map

